



Product Description:

EkoRip 220 is a tear tape made from **Certified FSC Paper** that is environmentally friendly and recyclable. Due to its paper-based nature, it is easily tearable and also offers good tensile strength. This product is visually appealing to customers and provides a hassle-free function. Additionally, it is printable, which provides a good advertising option for businesses.

Product Specifications:

Properties	Test Method	Unit	Specification
Tape width tolerance	Bagla Internal Method	mm	± 0.1
Total tape thickness	AFERA 5006	µm	220 ± 10
Paper Gramage	ISO 536	g/m ²	150 ± 5
Glue Thickness	Weight	GSM	30 ± 5
Breaking strength	AFERA 5004	kgf/25mm	≥21
Elongation at break	AFERA 5004	%	≥12
Tensile modulus at 10% elongation	Bagla Internal Method	kgf/mm ²	≥75
Tear Strength	ISO 1974	m/N	≥1300
Peel adhesion to stainless steel	FINAT FTM 1	gf/25mm	≥500
Loop tack to glass	FINAT FTM 9	gf/25mm	≥500

Standard Putups	Features	Applications
<ul style="list-style-type: none"> Width: 2mm - 30 mm, Length: 5000m– 1,20,000m Core ID: 76mm, 152mm Colors: Brown, Red, White Wounding: Traverse wound 	<ul style="list-style-type: none"> Eco Friendly and Repulpable Quick box opening performance Homogenous visual appearance within final packaging 	<ul style="list-style-type: none"> Medium grade of corrugated board E-commerce mailers & envelopes Recommended for automatic production Printing optional

Additional Information

SHELF LIFE: The standard shelf life is 12 months from the date of manufacture. However, this depends on several factors such as storage conditions, handling etc.

DISPOSAL: Preferred options for disposal are: (1) recycling, SPI Code 7; (2) incineration with energy recovery; and (3) land fill.

STORAGE: Storage below 32°C (90°F) is recommended.

DISCLAIMER: The technical data contained herein are guides to the use of Bagla® products. Bagla Group makes no guarantees of results and assumes no obligations or liability in connection with its advice.