

EkoPaper®

Description:

Designed using **FSC Certified Semi Crepe paper** and water based acrylic adhesive, EkoPaper packaging tape is an environmentally conscious yet affordable choice for superior strength and secure carton-sealing.



The mark of responsible forestry

TECHNICAL SPECIFICATIONS

| Physical Properties | | Value |
|------------------------------|--------|--------------------------------------|
| Total Thickness | D-3652 | 85gsm |
| Paper Grammage | | 57gsm |
| Glue Thickness | | 28gsm |
| Backing Material | | FSC™ Certified Semi-Crepe Paper Tape |
| Adhesive | | Water Based Acrylic |
| Adhesion To Steel (gms/25mm) | D-3330 | 700 |
| Shear Strength (mins) | A-5012 | 120 |
| Elongation (%) | D-3759 | 6 |
| Color | | Brown |

ADDITIONAL INFORMATION

STORAGE CONDITON: It is recommended to store the tape in a clean, dry environment, ensuring that the packaging remains intact and undamaged. Avoid storing it near volatile solvents. The ideal storage temperature of 70°F (21°C) ± 6°F with a relative humidity of 40% to 50% is recommended. Regularly rotating inventory is also advised to maintain product quality.

DISCLAIMER: The technical data contained herein are guides to the use of Bagla® products. Bagla Group makes no guarantees of results and assumes no obligations or liability in connection with its advice.

SHELF LIFE: The standard shelf life is 24 months from the date of manufacture. However, this depends on several factors such as storage conditions, handling etc.

