



Made with FSC™ Certified Paper

Designed using **FSC™ certified semi crepe paper** and water based acrylic adhesive, EkoPaper packaging tape is an environmentally conscious yet affordable choice for superior strength and secure carton-sealing.

KEY FEATURES



Less Thickness, Greater Strength

As compared to current offering of kraft paper in the market with 80gsm paper grammage, we have crafted our **EkoPaper tape using crepe paper with only 57gsm paper grammage**. This innovative design not only ensures a lighter and **more eco-conscious solution** but also maintains superior strength and durability.



Easy Printable Options

EkoPaper Tape offers easy printable options, allowing you to effortlessly add logos, messages, or branding elements **directly onto the tape**. Our printable tape option ensures **seamless integration** into your packaging process.



Strong Adhesion & High Tack

With **water-based acrylic**, we ensure that the tape has strong adhesion and the quality remains uncompromised. Also, this eco-friendly option is completely **repulpable** and **highly cost-effective**.



Hand Tearable & Easy-Unwinding

No more struggles with tape dispensers or searching for scissors. EkoPaper Tape is designed for convenience, allowing you to **tear it easily by hand without any hassle**. Its smooth and **effortless unwinding feature** saves you time and effort while ensuring secure carton sealing.



Cost Effective Solution

The reduced thickness not only contributes to its eco-friendly profile but also translates into **significant cost savings**. By utilizing less material without compromising on strength and performance, EkoPaper Tape offers a win-win solution.

TECHNICAL SPECIFICATIONS

Physical Properties		Value
Total Thickness	D-3652	85gsm
Paper Grammage		57gsm
Glue Thickness		28gsm
Backing Material		FSC™ Certified Semi-Crepe Paper Tape
Adhesive		Water Based Acrylic
Adhesion To Steel (gms/25mm)	D-3330	700
Shear Strength (mins)	A-5012	120
Elongation (%)	D-3759	6
Color		Brown



Order our **products samples** and discover their quality by yourself



ADDITIONAL INFORMATION

STORAGE CONDITON: It is recommended to store the tape in a clean, dry environment, ensuring that the packaging remains intact and undamaged. Avoid storing it near volatile solvents. The ideal storage temperature of 70°F (21°C) ± 6°F with a relative humidity of 40% to 50% is recommended. Regularly rotating inventory is also advised to maintain product quality.

DISCLAIMER: The technical data contained herein are guides to the use of Bagla® products. Bagla Group makes no guarantees of results and assumes no obligations or liability in connection with its advice.

SHELF LIFE: The standard shelf life is 24 months from the date of manufacture. However, this depends on several factors such as storage conditions, handling etc.

Head Office
• New Delhi, Delhi

Domestic Sales Office
• Delhi • Mumbai • Kolkata • Cochin
• Banglore • Hyderabad • Chennai • Bhopal

Factories
• 3 in Mundra, Gujarat, India
• 2 in Roorkee, Utrakhand, India
• 1 in Ghaziabad, Uttar Pradesh, India

International Sales Office
• Spain • USA • Australia • United Kingdom
• Argentina • South Africa • Egypt
• Poland • Germany • Canada

bagla | Let's innovate
GROUP | Packaging!