



### Product Description:

**Ezeerip** is produced from **80-micron high-density polyethylene (HDPE) film** and coated with a newly formulated pressure-sensitive adhesive. It is suitable for easy opening of packaging including corrugated cases, fibreboard cartons, envelopes, paper sacks, and e-commerce mailers.

### Product Specifications:

Properties	Test Method	Unit	Specification
Tape Width Tolerance	Bagla Internal Method	mm	± 0.1
Total Tape Thickness	AFERA 5006	µm	110 ± 10
Film Thickness	AFERA 5006	µm	80 ± 5
Breaking Strength	AFERA 5004	N/cm	≥52
Elongation at Break	AFERA 5004	%	≥30
Tensile Strength at Break	AFERA 5004	kgf/mm <sup>2</sup>	≥25
Tensile Modulus at 10% Elongation	Bagla Internal Method	kgf/mm <sup>2</sup>	≥95
Peel Adhesion to Stainless Steel	FINAT FTM 1	gf/25mm	≥800
Loop Tack to Glass	FINAT FTM 9	gf/25mm	≥800

### Standard Putups

- **Width:** 2.9mm to 30mm
- **Length:** Up to 40km
- **Core ID:** 152mm
- **Colors:** Clear + Multiple Colors
- **Wounding:** Traverse wound

### Features

- Rips easily through most grades of fluting and board.
- Enhances product strength & reinforces the weaker areas
- Utilise print for increased consumer engagement

### Applications

- Suitable for light corrugated boards i.e. single wall C/ B flute types
- Can be used for solid fibreboards as well (200-600g/m<sup>2</sup>)

### Additional Information

**SHELF LIFE:** The standard shelf life is 36 months from the date of manufacture. However, this depends on several factors such as storage conditions, handling etc.

**DISPOSAL:** Preferred options for disposal are: (1) recycling, SPI Code 7; (2) incineration with energy recovery; and (3) land fill.

**STORAGE:** Storage below 32°C (90°F) is recommended.

**DISCLAIMER:** The technical data contained herein are guides to the use of Bagla® products. Bagla Group makes no guarantees of results and assumes no obligations or liability in connection with its advice.