

**EzeeTear** tapes are thin, adhesive strips that are applied to packaging to make it easier to open. They are a popular choice because they have a built-in perforation that allows users to tear open the packaging effortlessly, without needing any additional tools. The simple and effective design of EzeeTear ensures hassle-free opening while keeping the packaging intact.

# PRODUCT INFORMATION

### **Key Features**

- Easy, intuitive and effortless opening for user convenience.
- Water-based pressure-sensitive acrylic adhesive bonds instantly without needing solvent, hot wax, or heating units.
- Extended spool lengths of upto 120km reduce the need for frequent changeovers.
- Highest safety standards for food-grade solutions.
- Superior quality minimizes downtime & wastage.
- Engaging print & optical security solutions to • elevate brand promotion.

## **Key Application Areas**

- FMCG industries: Food products, beverages, personal care & household products.
- Tobacco Industry
- Cosmetics Industry
- Pharmaceutical Industry
- Textile Industry

## **Standard Put-ups**

Backing:	MOPP			
Adhesive:	Water-based Acrylic			
Adhesive Activation:	Pressure Sensitive			
Thickness:	23, 26, 40 microns			
Width:	1.5mm to 4mm			
Length:	5,000m to 120,000m			
Core ID:	29, 76, 82.5, 125, 152mm			
Wounding:	Traverse wound			
Print:	Optional			



Blue Gold (Multiple colors available on request)

Red



()

Clear

Green

# **TECHNICAL SPECIFICATIONS**

Properties	Test Method	Unit	Film Thickness (Microns)		
			23µm	26µm	40µm
Tape Width Tolerance	Bagla Internal Method	mm	± 0.1	± 0.1	± 0.1
Total Tape Thickness	AFERA 5006	μm	34 ± 2	37 ± 2	51 ± 10
Film Thickness	AFERA 5006	μm	23 ± 2	26 ± 2	40 ± 2
Glue Thickness	Weight	GSM	11 ± 2	11 ± 2	11 ± 2
Breaking Strength	AFERA 5004	kgf/25mm	≥12	≥24	≥24
Elongation at Break	AFERA 5004	%	12 ± 5	15 ± 5	30 ± 5
Tensile Strength at Break	AFERA 5004	kgf/mm²	20 ± 5	≥40	40 ± 2
Peel Adhesion to Stainless Steel	FINAT FTM 1	gf/25mm	400 ± 10%	400 ± 10%	400 ± 10%
Loop Tack to Glass	FINAT FTM 9	gf/25mm	400 ± 10%	400 ± 10%	400 ± 10%

### Why Choose Bagla Group Tear Tapes?

- Monthly capacity of more than 1 million kilometres of tear tapes.
- New strategic factory locations in Indonesia & Paraguay as well with readily available stock.
- 10 fast speed European spooling machines.
- International raw material suppliers.
- Flexible and fast production time.
- All colours, lines, dots, and printing of upto 6 colours available.
- Sustainable options available.
- Personalised service and technical experts available for all your queries.





## **ADDITIONAL INFORMATION**

**SHELF LIFE:** The standard shelf life is 36 months from the date of manufacture. However, this depends on several factors such as storage conditions, handling etc.

DISPOSAL: Preferred options for disposal are: (1) recycling, SPI Code 7; (2) incineration with energy recovery; and (3) land fill.

**STORAGE:** Storage below 32°C (90°F) is recommended with Maximum Humidity of 80%, Protected from sunlight and away from the sources of heat or Ignition.

**DISCLAIMER:** The technical data contained herein are guides to the use of Bagla® products. Bagla Group makes no guarantees of results and assumes no obligations or liability in connection with its advice.

### Head Office

• New Delhi, Delhi

#### Factories

- 3 in Mundra, Gujarat, India
- 2 in Roorkee, Uttrakhand, India
- 1 in Ghaziabad, Uttar Pradesh, India

#### **Domestic Sales Office**

Delhi • Mumbai • Kolkata • Cochin
Banglore • Hyderabad • Chennai • Bhopal

#### International Sales Office

- Spain USA Australia United Kingdom
- Argentina South Africa Egypt
- Poland Germany Canada

