

**EzeeRip CE** is a high-performance, self-adhesive polypropylene tear strip featuring a synthetic rubber adhesive system. Optimized for high tensile strength. EzeeRip CE ensures reliable performance for medium to heavy grades of solid board applications.



### Product Features

- Superior tack.
- Excellent adhesion and high shear resistance on both corrugated and solid board surfaces.
- Strong backing ensures durability and strength.
- Ideal for high-speed unwinding in automated packaging lines.
- Unique co-extruded PP/PE backing delivers outstanding tear resistance, even with low overall thickness.

### Applications

- Medium to heavy solid board and double-wall corrugated cardboard applications.
- Preferred for automatic production.

## TECHNICAL SPECIFICATIONS

Properties	Test Method	Unit	Specifications
Tape Width Tolerance	Bagla Internal Method	mm	± 0.1
Total Tape Thickness	AFERA 5006	µm	111 ± 10
Film Thickness	AFERA 5006	µm	80 ± 5
Breaking Strength	AFERA 5004	N/cm	≥57
Elongation at Break	AFERA 5004	%	≥30
Tensile Strength at Break	AFERA 5004	N/cm	180
Peel Adhesion to Stainless Steel	FINAT FTM 1	gf/25mm	≥800
Loop Tack to Glass	FINAT FTM 9	gf/25mm	≥800

## ADDITIONAL INFORMATION

**SHELF LIFE:** The standard shelf life is 36 months from the date of manufacture. However, this depends on several factors such as storage conditions, handling etc.

**DISPOSAL:** Preferred options for disposal are: (1) recycling, SPI Code 7; (2) incineration with energy recovery; and (3) land fill.

**STORAGE:** Storage below 32°C (90°F) is recommended.

**DISCLAIMER:** The technical data contained herein are guides to the use of Bagla® products. Bagla Group makes no guarantees of results and assumes no obligations or liability in connection with its advice.