



Made with a MOPP backing & coated with a high-tack hotmelt adhesive, EzeeRip HM offers clean, effortless carton opening. The hotmelt formulation delivers instant, reliable bonding on both solid board & corrugated surfaces, while the dimensionally stable MOPP backing resists shrinkage and lift-off after application. EzeeRip HM is the ideal easy-open solution for pull-tab and tear-strip applications across shipping and retail packaging.

TECHNICAL SPECIFICATIONS

Properties	Test Method	Unit	Value
Film Thickness	AFERA 5006	µm	60 ± 10%
Total Thickness	AFERA 5006	µm	80 ± 10%
Backing Material	-	-	MOPP Film
Adhesive Type	-	-	Rubber-Based Hot Melt
Elongation at Break	AFERA 5004	%	30 ± 5%
Tensile Strength	AFERA 5004	N/cm	235
Adhesion to Steel	FINAT FTM 1	N/cm	7.25 (≈66.3 oz/in)

Standard Putups	Features	Applications
Adhesive: Hotmelt Width: 3mm to 25mm Length: 5,000m to 30,000m Core ID: 76mm, 152mm Colors: Clear + Multiple Colors Wounding: Traverse wound	- Bonds instantly & securely to solid and corrugated cardboard, with no lift-off or edge curl over time. - High tensile strength ensures a clean, straight tear without snapping mid-pull. - Resists shrinkage after application, maintaining seal integrity through storage and transit.	- Industrial & consumer cartons. - Corrugated shipping cartons and boxes. - Padded mailers, express delivery and courier envelopes. - E-commerce and retail-ready packaging with easy-open tear strips.

ADDITIONAL INFORMATION

SHELF LIFE: The standard shelf life of our tear tapes is 12 months, but if kept in optimal conditions, the tear tapes can be used upto 36 months.

DISPOSAL: Preferred options for disposal are: (1) recycling, SPI Code 7; (2) incineration with energy recovery; and (3) land fill.

STORAGE: Storage below 32°C (90°F) is recommended.

DISCLAIMER: The technical data contained herein are guides to the use of Bagla® products. Bagla Group makes no guarantees of results and assumes no obligations or liability in connection with its advice.